

Make / Model TOYOTA/COROLLA

Other

Year 1/2014-ON

Part number T2T628

Maximum towing capacity 1300 kg

Maximum ball load 130 kg

Bar weight 15 kg

Fit with wiring harness part No. EL5540

Fitting Instructions

Warning:

Safety First: Always use correct safety equipment.

This towbar is NOT to be drilled, cut, welded or modified in any way.

Check the surrounding area before drilling into chassis or body panels for fuel lines, wiring harnesses and other components that may be a hazard.

General:

Before fitting this towbar read fitting instructions and check installation hardware is correct.

Check that the towbar is suitable for the vehicle and be wary of any changes to the vehicle design that may conflict with the fitting of this towbar.

After drilling, blow any filings clear, remove any swarf and treat exposed metal with a rust inhibitor.

If this vehicle requires a bumper cut out, please check to make sure that you measure twice and check twice before cutting any panels as some bumper profiles can change.

If you are not sure then ask your towbar supplier.

Tighten all bolts as specified on the last page.

1. REMOVE OF BUMPER.
 - 1.1. SCREWS AND SCRIVETS IN WHEEL ARCHS /MUD FLAPS IF FITTED.
 - 1.2. REMOVE BOTH TAIL LIGHTS.
 - 1.3. REMOVE BUMPER PULLING OUT AT SIDES THEN REARWARDS.
2. REMOVE ALL BOLTS FROM TOWBAR TAKING NOTE OF LOCATIONS AND ASSEMBLY.
 - 2.1. REMOVE BOTH SHIPPING HOOKS AND DISCARD/REMOVE BOTH IMPACT CONES AND DISCARD.
 - 2.2. FIT TOWBAR ONTO VEHICLE USING M8 BOLTS AND WASHERS SUPPLIED/BOTTOM M10 BOLT TO BE INSTALLED AFTER DRILLING OUT HOLE FIRST.
 - 2.3. 4 X M12 BOLTS AND WASHERS TO BE INSTALLED FROM UNDERNEATH INTO EXISTING CAPTIVE NUTS.
 - 2.4. TIGHTEN ALL BOLTS TO SPECIFIED RATINGS.
3. REFIT BUMPER AND TAIL LIGHTS BACK ONTO VEHICLE.
4. INSTALL BALL MOUNT WITH M16 BOLTS AND WASHERS SUPPLIED AND TIGHTEN.
 - 4.1. ATTACH RATINGS STICKER TO DRIVERS SIDE DOOR PILLAR.

Metric GRADE 8.8	UNC GRADE 8
M6 – 12.5 Nm	3/8 – 50 Nm
M8 – 30 Nm	1/2 - 125 Nm
M10 – 60 Nm	5/8 – 245 Nm
M12 – 103 Nm	
M14 – 167 Nm	
M16 – 270 Nm	

Torque table for bolt tightening

