

# FITTING INSTRUCTIONS

PART NUMBER: **T4C606**



## Mitsubishi Triton Dual Cab W/Out Step – 8/09 onwards 3000 kg Towing Capacity/300 kg Ball Load Lug # L4045

- 1) Fit internal chassis rail brace into chassis rail.
- 2) Fit tow bar to outside of chassis rail with M12 bolts and nuts and washers.
- 3) Slide plate on wire with nut welded to it down to line up with forward most hole in tow bar and fit M12 bolts and washers.
- 4) Fit M12 bolt with square plate through bottom of chassis rail and fit nuts and washers from under chassis rail.
- 5) Fit M12 bolts, nuts and washers through most rearward holes in tow bar to join internal chassis rail brace together.
- 6) Tighten all bolts to torque listing.
- 7) Fit ball mount with pin and clip supplied.
- 8) Fit door sticker supplied to door.

**ECU MUST BE FITTED WITH THIS TOW BAR**  
**ECU SOLD SEPARATELY**

### RECOMMENDED ASSEMBLY TORQUE LISTING

<u>Diameter</u>	<u>Grade 8.8 Bolt</u>
	<b>Nm</b>
M6	9.5
M8	21.7
M10	43.4
M12	77.3
M16	189.8