

Make / Model FORD/MAZDA ESCAPE/TRIBUTE

Other

Year 02/01 ON

Part number T2F508

Maximum towing capacity 1600 kg
Maximum ball load 160 kg
Bar weight 18 kg

Fit with wiring harness part No. EL5804

Fitting Instructions

Warning:

Safety First: Always use correct safety equipment.

This towbar is NOT to be drilled, cut, welded or modified in any way.

Check the surrounding area before drilling into chassis or body panels for fuel lines, wiring harnesses and other components that may be a hazard.

General:

Before fitting this towbar read fitting instructions and check installation hardware is correct.

Check that the towbar is suitable for the vehicle and be wary of any changes to the vehicle design that may conflict with the fitting of this towbar.

After drilling, blow any filings clear, remove any swarf and treat exposed metal with a rust inhibitor.

If this vehicle requires a bumper cut out, please check to make sure that you measure twice and check twice before cutting any panels as some bumper profiles can change.

If you are not sure then ask your towbar supplier.

Tighten all bolts as specified on the la

st page.

1. REMOVAL OF BUMPER.
 - 1.1. OPEN TAILGATE, REMOVE PHILLIPS HEAD SCREWS/2 X EACH TAIL LIGHT, CAREFULLY REMOVE TAIL LIGHTS REARWARDS AS THERE ARE LOCATING PINS.
 - 1.2. REMOVE SCREWS/ TOP MIDDLE SECTION OF BUMPER, WHEEL ARCHES AND 2X 14MM NUTS IN BEHIND BUMPER.
 - 1.3. ONCE BUMPER IS REMOVED TAKE EXHAUST OFF REAR HANGERS, DRILL REAR POP RIVET FOR HEAT SHIELD, PULLING DOWN TO EXPOSE OPENING.
 - 1.4. REMOVE IMPACT BEAM AND DISCARD.
2. REMOVE ALL BOLTS FROM TOW BAR.
 - 2.1. PLACE TOWBAR ARMS INTO OPENING OF REAR SUB FRAME; SECURE WITH ½ INCH UNC BOLTS, WASHERS AND PLATES FROM UNDERNEATH VEHICLE.
 - 2.2. FIT U BOLT FACING DOWN ONTO CENTRE SHIPPING HOOK AND TIGHTEN ALL BOLTS FOR TOWBAR.
 - 2.3. RE-ATTACH HEAT SHIELD AND EXHAUST.
3. RE-ATTACH BUMPER AFTER CUT OUT HAS BEEN DONE.
 - 3.1. ATTACH RATINGS STICKER TO DRIVERS SIDE DOOR PILLAR.

Torque table for bolt tightening

Metric GRADE 8.8	UNC GRADE 8
M6 – 12.5 Nm	3/8 – 50 Nm
M8 – 30 Nm	1/2 - 125 Nm
M10 – 60 Nm	5/8 – 245 Nm
M12 – 103 Nm	
M14 – 167 Nm	
M16 – 270 Nm	

MAKE / MODEL / YEAR