

# FITTING INSTRUCTIONS



PART NUMBER: T2K544

Kia Cerato - 07/09 on  
Towing Capacity 1200Kg / Ball Load 120 Kg  
Lug # L270C

- 1) Remove 3x screws from inside wheel arch and 1x screw in top of bumper in side wheel arch. And 1x 10mm bolt from under side at the bottom of the wheel arch, both sides.
- 2) Pull out plastic push clips from inside boot to expose the rear of the tail lights, undo 3x 10mm nuts then unplug and remove tail light both sides unplug reversing sensors on passenger side.
- 3) Remove 3x plastic push pull clips from under side of bumper and 2x push pull clips from under tail light, both sides.
- 4) From underneath undo 2x 14mm bolts that hold the impact beam in place.
- 5) Gently peel bumper away starting at the wheel arch, and remove bumper.
- 6) Remove impact beam from bumper and discard.
- 7) From underneath loosely screw angle brackets to chassis rails.
- 8) Offer tow bar to vehicle and insert 1x M10 x 35mm bolt and flat washer through angle bracket out through beaver panel and through tow bar loosely fit flat washer and spring washer and nut, both sides.
- 9) Insert M10 bolts and flat washers through remaining holes, and loosely fit the flat washer's and spring washers and nuts.
- 10) Insert M10 x 35mm bolt and spring washer through plate and insert through shipping hook underneath and fit M10 whizz nut.
- 11) Tighten all bolts and refit bumper.

**RECOMMENDED ASSEMBLY  
TORQUE LISTING**

<u>Diameter</u>	<u>Grade 8.8 Bolt</u>	<u>Nm</u>
M6		9.5
M8		21.7
M10		43.4
M12		77.3
M16		189.8

