

FITTING INSTRUCTIONS



PART NUMBER: **T4C284**

Mitsubishi Pajero 05/00 - on
3000 kg Towing Capacity/250 kg Ball Load
Lug # L4240 – ECU required for models from 11/06 - on

- 1) **NP MODELS ONLY REQUIRE A CUT OUT.** Find the centre of bumper bar and mark 40mm each side of centre and 120mm from edge of bumper.
- 2) Remove two bolts holding bumper bar to brace.
- 3) Lower air con unit on drivers' side at rear if fitted.
- 4) Remove centre brace by removing four bolts each side. Two into bottom of chassis, one on the inside of chassis and one long bolt through chassis from the outer side of the chassis rail and retain.
- 5) Fit tow bar to vehicle using original bolts. **Note:** with long bolt fit nut welded to plate on wire supplied.
- 6) Tighten all bolts to torque listing.
- 7) Refit air con unit if removed.
- 8) Fit ball mount with pin and clip supplied.
- 9) Fit door sticker supplied to door

ECU SOLD SEPARATELY

RECOMMENDED ASSEMBLY TORQUE LISTING

<u>Diameter</u>	<u>Grade 8.8 Bolt</u>
	Nm
M6	9.5
M8	21.7
M10	43.4
M12	77.3
M16	189.8