

FITTING INSTRUCTIONS



PART NUMBER: T2Z017

Hyundai Accent Hatch 3 & 5 Door 6/00 to 05
Towing Capacity 700 Kg / Ball Load 50 Kg
Lug # L203

- 1) Lower exhaust.
- 2) Remove bumper clips from underneath.
- 3) Fit towbar over exhaust and up to outside of chassis rail.
- 4) Fit 4x M12 bolts & washers into side of chassis rail into captive nuts.
- 5) Fit M12 bolt, washer & plate through shipping hook and into threaded plate on towbar.
- 6) Tighten all bolts to torque listing below.
- 7) Fit tongue with tongue bolts supplied.
- 8) Fit door sticker supplied to door.
- 9) Refit exhaust
- 10) Refit bumper clips.

RECOMMENDED ASSEMBLY
TORQUE LISTING

<u>Diameter</u>	<u>Grade 8.8 Bolt</u>
	Nm
M6	9.5
M8	21.7
M10	43.4
M12	77.3
M16	189.8

FITTING INSTRUCTIONS



PART NUMBER: T2Z017

Hyundai Excel Hatch Odd Chassis Rail 1998 to 2000
Towing Capacity 600 Kg / Ball Load 50 Kg
Lug # L203

- 1) Lower exhaust.
- 2) Remove bumper clips from underneath.
- 3) Fit towbar over exhaust and up to outside of chassis rail on right hand side and inside chassis rail on left hand side.
- 4) Fit 4x M12 bolts & washers into side of chassis rail into captive nuts.
- 5) Fit M12 bolt, washer & plate through shipping hook and into threaded plate on towbar.
- 6) Tighten all bolts to torque listing below.
- 7) Fit tongue with tongue bolts supplied.
- 8) Fit door sticker supplied to door.
- 9) Refit exhaust
- 10) Refit bumper clips.

**RECOMMENDED ASSEMBLY
TORQUE LISTING**

<u>Diameter</u>	<u>Grade 8.8 Bolt</u>
	Nm
M6	9.5
M8	21.7
M10	43.4
M12	77.3
M16	189.8

FITTING INSTRUCTIONS



PART NUMBER: T2Z017

Hyundai Excel Sedan 1998 to 2000
Towing Capacity 600 Kg / Ball Load 50 Kg
Lug # L231

- 1) Lower exhaust.
- 2) Remove bumper clips from underneath.
- 3) Fit towbar over exhaust and up to outside of chassis rail.
- 4) Fit 4x M12 bolts & washers into side of chassis rail into captive nuts.
- 5) Fit M12 bolt, washer & plate through shipping hook and into threaded plate on towbar.
- 6) Tighten all bolts to torque listing below.
- 7) Fit tongue with tongue bolts supplied.
- 8) Fit door sticker supplied to door.
- 9) Refit exhaust
- 10) Refit bumper clips.

**RECOMMENDED ASSEMBLY
TORQUE LISTING**

<u>Diameter</u>	<u>Grade 8.8 Bolt</u>
	Nm
M6	9.5
M8	21.7
M10	43.4
M12	77.3
M16	189.8